

DFR

Direct to Film Remover

AlbaChem® DFR Direct to Film Remover removes DTF graphics from all types of fabrics. A strong solvent blend attacks DTF binder, allowing the graphic image to be peeled or scraped away.

- ALL TEXTILES
- LOW ODOR
- WATER SOLUBLE

Directions for use

Unscrew spout cap. Puncture the center of the white plastic seal. Replace spout cap. Twist to open and close. Follow the steps below to remove the print using DFR.

1. **Apply DFR**
   Apply DFR to the fabric underside directly beneath the print area you want to remove. Wait approximately 1 to 5 minutes for DFR to penetrate. For best results, let it rest for at least 3 minutes after application; the DTF print will be easier to remove with less residue.
2. **Remove the print**
   Gently peel or scrape off the print material. If necessary, drip DFR directly on top of the print, then peel or scrape away the remaining image.
3. **Clean remaining residue**
   Apply additional DFR to a clean, textured cloth (e.g. terrycloth), and wipe away any remaining residue.
4. **Rinse and dry**
   Rinse the area thoroughly with water to flush out any remaining DFR, then run through a washing machine. Blot away excess moisture and allow the fabric to dry. For quicker results, heat press the area to speed up drying.
5. **Reprint**
   Once the fabric is completely dry, the area is ready for reprinting.

Technical data

PHYSICAL PROPERTIES

Appearance	Clear colorless liquid
Solubility in water	Yes
Odor	Mild solvent

ENVIRONMENTAL

Volatile Organic Compound (VOC)	**50%**
Hazardous Air Pollutant (HAP)	**No**
Ozone Depleting Substance	**No**
SARA 313 Chemicals	**No**

Consult safety data sheet for all safety and handling information.