IColor™ TOP SEAL™

The IColor™ TOP Seal™ Finishing Sheet is designed to elevate the post-press process of your t-shirt or textile heat transfers. Engineered with a specialized silicone coating, this finishing sheet seamlessly embeds the transfer into the garment's fibers, ensuring enhanced durability and an additional layer of protection against wash-induced wear. Its superior technology safeguards the vibrancy of your prints, preserving their brilliance over time.

Use in place of kraft paper for the post press only! The IColor™ TOP Seal™ is REUSABLE from 350 up to 500 presses.

For use with White Toner and DTF prints!

INSTRUCTIONS FOR BEST RESULTS:

1) Before the first use, press the sheet with the rubber side down on the lower platen of your heat press with media pressure for 20 seconds at 270° F / 132° C. This will condition the TOP Seal properly. The back side of the product is the slick, glossy side.
2) Press and peel your transfer according to the instructions for the particular transfer paper you are using.
3) For the final post press, use the rubbery side toward the decoration and press for 20 seconds with heavy pressure at a temperature between 270° - 290° F (132° - 143° C).

Important:

- Use the IColor™ TOP Seal™ in place of kraft paper for the final post press only!
- Do not cut the sheet in any way or the rubber film will come apart.
- Do not use with any CP Toner because the yellow pigments will migrate into the rubber film.
- Do not use with sublimation ink or toner, or sublimation printed garments or products.
- Recommended temperature tolerance is 270° - 290° F (132° - 143° C). Do not use above 300° F / 150° C to avoid premature degradation of the product.

Experience the difference the IColor™ TOP Seal™ Finishing Sheet can make in enhancing the longevity and vibrancy of your textile heat transfers!



